

S 300 6 000

wyłączniki nadprądowe S 301, S 302
charakterystyka B i C



6055 10



6056 08



6055 31



6056 30



Wymiary (str. 328)
Dane techniczne (str. 328)
Charakterystyki (str. 329)

Zdolność zwarciorowa:

6 000 EN 60898

Pak.	Nr ref.	Jednobiegunowe 230/400 V~		
		Prąd znamionowy I_n	Szerokość w modułach 17,5 mm	Produkt
	Charakterystyka B			
12/72	6055 06	6 A	1	S 301 B-6
1/54	6055 07	8 A	1	S 301 B-8
12/72	6055 08	10 A	1	S 301 B-10
1/54	6055 09	13 A	1	S 301 B-13
12/72	6055 10	16 A	1	S 301 B-16
12/72	6055 11	20 A	1	S 301 B-20
12/72	6055 12	25 A	1	S 301 B-25
12/72	6055 13	32 A	1	S 301 B-32
1/54	6055 14	40 A	1	S 301 B-40
1/54	6055 15	50 A	1	S 301 B-50
1/54	6055 16	63 A	1	S 301 B-63
	Charakterystyka C			
1/54	6056 00	0,3 A	1	S 301 C-0,3
1/54	6056 01	0,5 A	1	S 301 C-0,5
1/54	6056 02	1 A	1	S 301 C-1
1/54	6056 03	2 A	1	S 301 C-2
1/54	6056 04	3 A	1	S 301 C-3
1/54	6056 05	4 A	1	S 301 C-4
12/72	6056 06	6 A	1	S 301 C-6
1/54	6056 07	8 A	1	S 301 C-8
12/72	6056 08	10 A	1	S 301 C-10
1/54	6056 09	13 A	1	S 301 C-13
12/72	6056 10	16 A	1	S 301 C-16
12/72	6056 11	20 A	1	S 301 C-20
12/72	6056 12	25 A	1	S 301 C-25
12/72	6056 13	32 A	1	S 301 C-32
1/54	6056 14	40 A	1	S 301 C-40
1/54	6056 15	50 A	1	S 301 C-50
1/54	6056 16	63 A	1	S 301 C-63

Pak.	Nr ref.	Dwubiegunowe 400 V~		
		Prąd znamionowy I_n	Szerokość w modułach 17,5 mm	Produkt
	Charakterystyka B			
6/36	6055 26	6 A	2	S 302 B-6
1/24	6055 27	8 A	2	S 302 B-8
6/36	6055 28	10 A	2	S 302 B-10
1/24	6055 29	13 A	2	S 302 B-13
6/36	6055 30	16 A	2	S 302 B-16
6/36	6055 31	20 A	2	S 302 B-20
6/36	6055 32	25 A	2	S 302 B-25
6/36	6055 33	32 A	2	S 302 B-32
1/24	6055 34	40 A	2	S 302 B-40
1/24	6055 35	50 A	2	S 302 B-50
1/24	6055 36	63 A	2	S 302 B-63
	Charakterystyka C			
1/24	6056 20	0,3 A	2	S 302 C-0,3
1/24	6056 21	0,5 A	2	S 302 C-0,5
1/24	6056 22	1 A	2	S 302 C-1
1/24	6056 23	2 A	2	S 302 C-2
1/24	6056 24	3 A	2	S 302 C-3
1/24	6056 25	4 A	2	S 302 C-4
6/36	6056 26	6 A	2	S 302 C-6
1/24	6056 27	8 A	2	S 302 C-8
6/36	6056 28	10 A	2	S 302 C-10
1/24	6056 29	13 A	2	S 302 C-13
6/36	6056 30	16 A	2	S 302 C-16
6/36	6056 31	20 A	2	S 302 C-20
6/36	6056 32	25 A	2	S 302 C-25
6/36	6056 33	32 A	2	S 302 C-32
1/24	6056 34	40 A	2	S 302 C-40
1/24	6056 35	50 A	2	S 302 C-50
1/24	6056 36	63 A	2	S 302 C-63